

UNITED STATES DEPARTMENT OF THE INTERIOR
NATIONAL PARK SERVICE

**NATIONAL REGISTER OF HISTORIC PLACES
INVENTORY -- NOMINATION FORM**

FOR NPS USE ONLY	
RECEIVED	JUN 17 1980
DATE ENTERED	OCT 22 1981

CONTINUATION SHEET

ITEM NUMBER 7 PAGE 43/47

San Juan Light

NAME: Historic: Faro de las Cabezas de San Juan
Common: Cabo San Juan Light

LOCATION: On the north easterly part of the highest point of Cape San Juan on the north easterly point of Puerto Rico. On position 18° 23' N - 65° 37.1' W.

CLASSIFICATION: Occupied. Restricted access.

DESCRIPTION: Excellent condition. Altered. Original site.
In 1782, one hundred years before the final construction of Cabo San Juan Lighthouse, Fray Iñigo Abbad y Lasierra, who wrote the first formal history of Puerto Rico, stated that

The mountain peaks of Loquillo and Laivonito ... can be seen from a far off distance in the sea, and through them sailors recognize Cabezas de San Juan, the reference point of those who regularly navigate by these islands /to direct their course/ towards the Honduras and Mexico Gulf.

His "message" began to materialize by mid 1850 when feasibility plans were drawn to build a lighthouse in Cabo San Juan. The location was carefully surveyed and studied in October 1856 concurring with today's light location. In 1876 the first plans were commissioned and construction began in early 1877. The original 1876 plans have not been found yet but subsequent references --particularly in 1881-- clearly indicate that the earliest project was dropped. The reasons are unknown but it was possible that budgetary problems might have been the cause. There are further indications that by 1880 another plan was considered and construction carried out. This second plan apparently served as the basis for the last attempt, 1881, upon which the actual structure was built.

In March 1882, one hundred years after Abbad y Lasierra's remarks, the builder delivered the construction to the Colonial Governor of Puerto Rico. On 2 May 1882 it was officially lighted. The original white building with dark gray trimmings, green doors and windows, became the second lighthouse be built according to the plans ... and remained almost unaltered for another hundred years.

UNITED STATES DEPARTMENT OF THE INTERIOR
NATIONAL PARK SERVICE

**NATIONAL REGISTER OF HISTORIC PLACES
INVENTORY -- NOMINATION FORM**

FOR NPS USE ONLY

RECEIVED

JUN 17 1980

DATE ENTERED

OCT 22 1981

CONTINUATION SHEET

ITEM NUMBER 7 PAGE 45/47

The 4.5 mts. (od) cylindrical tower is 13.35 mts. to the top of the brick and stone circular lantern. An elaborate and richly decorated cast-iron stairway leads to the lantern. The tower has 3.2 mts. internal diameter and opens to the north through a large window opposite the tower's double wooden door opening to the roof. The lantern is formed by an external circular wall 2.5 mts. in diameter which encases a cast-iron circular lantern. A circular corridor separates the cast-iron lantern from the external brick and stone wall.

The original 3rd order lantern, in cast-iron, copper, and glass was severely damaged by the 1932 hurricane. The original illuminating apparatus was apparently changed in the early 1900's. It is known, though, that the original light characteristics were not changed until after 1898: it was a 3rd order light with 18 miles range and showed a fixed white light with red flashes every 3 minutes. A 1902 description of the apparatus states that it was a lenticular, 1881, Sautter, Lemonnier & Cie. 3rd order fixed white light varied by red flashes, 1 mt. in diameter lens. It fully revolved every 9 minutes. It had 5 panels in stationary section and 6 panels in the central drum of which three produced the red flashes. In each panel of the central drum there were 7 annular rings including a bull's eye. The lens had 11 prisms on each panel above the central drum and 4 below. The flashes were produced by the revolving central drum. The revolving mechanism was mounted on a chariot activated by a clock work which clock cord passed over 2 sheaves to a drop tube in the east side of tower. The cord had a 254 lb. weight.

The evidence indicates this lens was removed in 1916 and replaced by a 1881 lenticular Barbier & Bernard, Reiver & Cie. 4th order, 50 cms. in diameter flashing white lens. It had 4 panels of which two were flashing. Each panel of the central drum had 5 annular rings. Four prisms were located on each panel above the central drum and 2 below. The original chariot system was apparently replaced by a ball system. The clock system was left in place.

This lens, the lantern, and possibly the clock system were damaged, or totally destroyed, by the hurricane. A new lens was installed: a U.S. Westinghouse four-way revolving beacon with four flashing panels 1 mt. in diameter. The lamp is enclosed in a spherical dioptic lens. This is the light apparatus which today shows Fl. W 15s. with a 26 mile range, the largest in the Island.

The structure went through several alterations. The brick and stone balustrade that surrounded the lantern was replaced, possibly in 1932, by an iron one. The original floor plan was redone possibly in the 1940's or early 1950's. Two of the bedrooms were transformed into bathrooms. The east and west vestibule walls were torn down and replaced

UNITED STATES DEPARTMENT OF THE INTERIOR
NATIONAL PARK SERVICE

**NATIONAL REGISTER OF HISTORIC PLACES
INVENTORY -- NOMINATION FORM**

FOR NPS USE ONLY	
RECEIVED	JUN 17 1980
DATE ENTERED	OCT 22 1981

CONTINUATION SHEET

ITEM NUMBER

7

PAGE 46/47

by reinforced concrete beams; the north walls of both old livingrooms were also torn down and replaced by concrete beams. Thus, this allowed for the reduction of the old engineer's room and storeroom from which the new kitchens were built.

Nevertheless, the 1880-1881 firewood beams and lattice which formed the old brick roof were totally left intact. The ausubo beams (4" x 9") form a lovely rectangular pattern with the crossing ausubo lattice (2" x 3"). These keep in place 6 superimposed layers of brick (2" x 5 3/4" x 11 1/2") which form a massive (15") roof.

Furthermore, most of the interior woodwork (doors), gray and white Genoa marble slabs, elaborate cast-iron tower stairway are in place. The structure reveals that special attention was given to its harmonious decorative elements: the upper middle section of the portico is adorned by a simple moulding that is at the same height of the main entrance's heavy and elaborate hood moulding. The portico, being higher than the dwelling itself, but showing the same heavy and elaborate cornice, provides a formal presence to the facade that is enhanced by the parapet in the portico's roof built in a balustrade fashion. This parapet is not repeated anywhere else in the structure but in the old parapet of the old lantern which showed --c. 1898 photo-- a brick and mortar balustrade.

This same balustrade rested on simple concave brackets which are the reverse shape of the portico's moulding. All these elements give the lighthouse a certain "castle" appearance, a peculiar counterbalance to the rest of the neo-classic structure which sole decoration is its heavy cornice. The tower has a decoration of its own in its middle section in an embracing rectangular cornice that projects itself, from its own center, to the outside in a convex shape.

SIGNIFICANCE: Is the second oldest lighthouse on the Island and so far the best structurally preserved. It formed the crucially important most north eastern light angle in the north and eastern light belts guiding transportation into the Vieques and Culebra Passages to the Caribbean and Atlantic Ocean.

GEOGRAPHICAL DATA: Area nominated: approximately 1.55 acres. Boundary description: beginning at a point S 62° 50' E 138 ft from NW corner of dwelling; thence N 49° 30' W 373.6 ft to a point; thence S 31° W 265 ft to a point; thence S 41° 40' E 28.07 ft to a point; thence S 75° E 214 ft to a point; thence N 78° 30' E 176 ft to a point; thence N 41° E 35 ft to the point of beginning.

UNITED STATES DEPARTMENT OF THE INTERIOR
NATIONAL PARK SERVICE

**NATIONAL REGISTER OF HISTORIC PLACES
INVENTORY -- NOMINATION FORM**

FOR NPS USE ONLY
RECEIVED JUN 17 1980
DATE ENTERED OCT 22 1981

CONTINUATION SHEET

ITEM NUMBER 7 PAGE 47/47

SUPPORTING MATERIALS: v. attached pocket #15 "Cabo San Juan Light".
Enclosures are: Quadrangle; plan area nominated; c. 1898 photo; 1978
photos; blue copies original site drawings; alterations' drawings,